

**GENERAL PURPOSE
BASE MOUNTED
Single Phase**



Cat. #4377

Features

- Sleeve or ball bearings
- Reversible rotation

Applications

Designed for applications having moderate starting loads or loads applied after the motor is up to speed, like commercial fans and blowers and evaporative coolers.

**GENERAL PURPOSE
BASE MOUNTED
Single Phase**



Cat. #H901

Features

- Sleeve or ball bearings
- Reversible rotation

Applications

Designed for applications having moderate starting loads or loads applied after the motor is up to speed, like commercial fans and blowers and evaporative coolers.

Split Phase – Dripproof – Resilient Base

HP	RPM	Volts	NEMA Frame	SF	PROT	Base	FLA @ NP	Catalog No.	List Price	Notes
1/6	1725	115	48	1.35	None	RB	3.9	4304	\$ 98	4
	1725	115	48	1.35	Auto	RB	3.9	4314	101	4
	1140	115	48	1.35	None	RB	4.0	H112	162	4
	1140	115	48	1.35	Auto	RB	4.0	H113	168	4
1/4	1725	115	56Z	1.00	Auto	RB	5.7	4364	114	1,4,7
	1725	115	48	1.00	Auto	RB	5.7	4301	103	4
	1725	115	48	1.35	Auto	RB	5.1	4305	107	4
	1725	115	48	1.35	None	RB	5.1	4355	103	4
	1725	115	48	1.00	None	RB	5.7	4352	100	4
	1725	115	56Z	1.00	None	RB	5.7	4359	111	1,4,7
	1725	115/230	48Y	1.35	Auto	RB	5.2/2.6	4702	109	1,4,7
	1725	230	48	1.35	Auto	RB	2.5	4306	118	4
	1725	230	48	1.35	None	RB	2.5	4360	114	4
	1425	110/220	56Z	1.00	Auto	RB	5.2/2.6	H690	160	50
	1/3	3450	115	48	1.35	None	RB	5.6	H114	133
3450		115	48	1.35	Auto	RB	5.6	H115	141	
1725		115	48	1.00	Auto	RB	6.2	4310	113	4
1725		115	48	1.00	None	RB	6.2	4369	110	4
1725		115	48	1.00	None	RB	6.6	H674	143	
1725		115	48	1.35	None	RB	6.2	4370	143	
1725		115	56Z	1.00	None	RB	6.2	4377	121	1,4,7
1725		115	48	1.35	Auto	RB	5.6	4308	146	
1725		115	56Z	1.35	None	RB	5.5	4050	168	
1725		115	56Z	1.00	Auto	RB	6.2	4381	124	1,4,7
1725		115/230	48Y	1.35	Auto	RB	6.0/3.0	4707	121	1,4,7
1725		230	48	1.35	Auto	RB	3.1	4309	156	
1725		230	48	1.00	None	RB	3.3	4371	121	4,7
1725		230	48	1.00	Auto	RB	3.3	4311	124	4
1425		110/220	56Z	1.00	Auto	RB	7.0/3.5	H692	172	1,7,50
1425		220	56Z	1.00	None	RBE	3.5	H673	163	4,7,50
1/2		1725	115	56	1.25	Auto	RB	7.9	4392	176
	1725	115	56	1.25	None	RB	7.9	4390	173	
	1725	115	56	1.00	None	RB	8.3	4386	170	
	1725	115/230	48Y	1.25	Auto	RB	7.6/3.8	4709	148	1,4,7
	1725	230	56	1.00	Auto	RB	4.2	4602	185	
	1725	230	56	1.00	None	RB	4.2	4387	180	
	1725	230	56	1.25	Auto	RB	4.5	4393	188	
	1425	110/220	56	1.00	Auto	RB	9.2/4.6	H693	191	50
	3/4	1725	115	56	1.00	None	RB	11.2	4422	212
1725		115	56	1.00	Auto	RB	11.4	4338	220	

Split Phase – Dripproof – Resilient Base – Steel Endshields

HP	RPM	Volts	NEMA Frame	SF	PROT	Base	FLA @ NP	Catalog No.	List Price	Notes
1/6	1725	115	48Z	1.35	Auto	RB	4.4	H913	\$104	9
1/4	1725	115	48Z	1.35	Auto	RB	5.6	H915	112	9
1/3	1725	115	48Z	1.35	Auto	RB	6.9	H917	128	9
1/2	1725	115	48Z	1.25	Auto	RB	8.7	H919	157	10

Split Phase – Dripproof – Welded Base – Steel Endshields

1/4	1725	115	48Z	1.15	Auto	WBE	5.1	H902	\$ 89	9
	1725	115	48Z	1.15	None	WBE	5.1	H901	85	9
1/3	1725	115	48Z	1.15	None	WBE	5.5	H903	88	9
	1725	115	48Z	1.15	Auto	WBE	5.5	H904	91	9
1/2	1725	115	56Z	1.15	Auto	WBE	8.1	H906	107	10
	1725	115	56Z	1.15	None	WBE	8.1	H905	103	10
3/4	1725	115	56Z	1.00	None	WBE	11.2	H907	126	10
	1725	115	56Z	1.00	Auto	WBE	11.2	H908	130	10

Split Phase – Dripproof – Welded Base

1/6	1725	115	48	1.35	Auto	WB	3.9	4349	\$ 97	4
1/4	1725	115	48	1.35	None	WB	5.1	4354	99	4
	1725	115	48	1.35	None	WB	5.6	H239	133	7
	1725	115	48	1.00	None	WB	5.7	4351	95	4
	1725	115	48	1.35	Auto	WB	5.1	4362	102	4
1425	110/220	48	1.00	Auto	WB	5.2/2.6	H689	155	7,50	
1/3	1725	115	56Z	1.00	None	WB	6.2	4372	116	1,4,7
	1725	115	48Z	1.00	None	WB	6.2	4376	113	4,21
	1725	115	48	1.00	Auto	WB	6.2	4380	109	4
	1725	115	56Z	1.00	None	WB	6.2	H676	138	7
	1725	115	48	1.00	None	WB	6.2	4368	106	4
	1725	115	48	1.00	None	WB	6.8	H229	138	7
	1725	230	48	1.00	None	WB	3.3	4373	119	4,7
	1425	110/220	48	1.00	Auto	WB	7.0/3.5	H691	166	7,50
1/2	1725	115	56	1.00	None	WB	8.3	H230	181	
	1725	115	48	1.00	None	WB	8.3	H696	164	7



GE Commercial Motors

By REGAL-BELOIT

**GENERAL PURPOSE
BASE MOUNTED
Single Phase**



Cat. #C223

Features

- Sleeve or ball bearings
- Reversible rotation
- Selected Energy Saver (◆) designs available

Applications

Designed for applications having hard or heavy-duty starting loads, like industrial blowers, pumps and machinery.

Capacitor Start – Dripproof – Resilient Base

HP	RPM	Volts	Frame	SF	PROT	Base	@ NP	No.	Price	Notes
1/4	1725	115	48	1.35	Auto	RB	5.2	C201	\$151	4
	1725	115	48	1.35	None	RB	5.2	C200	147	4
	1725	115/230	48	1.35	None	RB	5.2/2.6	C202	153	4
	1725	115/230	48	1.35	Auto	RB	F	C203	156	4
	1425	110/220	48	1.35	Auto	RB	5.6/2.8	C460	190	50
	1140	115/230	56	1.35	Auto	RB	6.2/3.1	C544	272	
1/3	3450	115/230	48	1.35	Auto	RB	6.8/3.4	C208	160	
	1725/1425	100-120/200-240	56	1.35	Auto	RB	4.0-3.8/2.0-1.9	E254◆	227	36,84
	1725/1425	115/208-230	48	1.35	None	RB	6.0/3.2-3.0	C209	182	84
	1725/1425	115/208-230	48	1.35	Auto	RB	6.0/3.2-3.0	C210	192	84
	1725/1425	115/208-230	56	1.35	None	RB	6.0/3.2-3.0	C215	197	84
	1725/1425	115/208-230	56	1.35	Auto	RB	6.0/3.2-3.0	C216	202	84
	1725	115/230	48	1.00	Auto	RB	6.4/3.2	C129	152	4
	1725	115/230	48	1.00	Man	RB	6.4/3.2	C1432	157	4
	1425	110/220	56	1.35	Auto	RB	7.4/3.7	C457	230	50
	1425	110/220	56	1.35	None	RB	7.4/3.7	C1431	224	50
	1140	115/230	56	1.35	None	RB	8.6/4.3	C1258	267	
	1140	115/230	56	1.35	Auto	RB	8.6/4.3	C548	275	
1/2	1725/1425	100-120/200-240	56	1.25	Auto	RB	5.8-5.6/2.9-2.8	E263◆	272	36,84
	1725	115/208-230	56	1.25	None	RBE	8.8/4.2-4.4	C221	208	
	1725	115/230	56	1.25	Auto	RB	8.8/4.4	C223	212	
	1725	115/230	48	1.00	Auto	RB	8.2/4.1	C133	208	
	1725	115/230	56	1.00	Auto	RB	8.2/4.1	C136	219	
	1425	110/220	56	1.25	Auto	RB	9.2/4.6	C439	263	50
	1425	110/220	56	1.25	None	RB	9.2/4.6	C438	257	50
	1140	115/230	56	1.25	None	RB	9.4/4.7	C1264	381	
	1140	115/230	56	1.25	Auto	RB	9.4/4.7	C552	389	
3/4	1725/1425	100-120/200-240	56	1.25	Auto	RB	9.0-8.8/4.5-4.4	E272◆	338	36,84
	1725	115/208-230	56	1.25	Auto	RB	11.4/5.6-5.7	C138	237	
	1725	115/208-230	56	1.25	None	RBE	13.2/6.2-6.6	C230	246	
	1725	115/230	56	1.25	Auto	RB	13.2/6.6	C231	250	
	1425	110/220	56	1.25	None	RB	12.2/6.1	C1433	303	50
	1425	110/220	56	1.25	Auto	RB	12.2/6.1	C1187	312	50
	1140	115/230	56	1.15	None	RB	12.6/6.3	C232	440	36
1	1725/1425	100-120/200-240	56	1.15	Auto	RB	11.8-11.4/5.9-5.7	E281◆	355	36,84
	1725	115/208-230	56H	1.15	None	RB	13.6/6.7-6.8	C235	285	
	1725	115/230	56	1.15	Auto	RB	13.6/6.8	C236	282	
	1725	115/230	56	1.00	Auto	RB	14.4/7.2	C636	291	
1.5	1725	115/208-230	56H	1.15	Auto	RB	18.2/9.1	C239	331	36

◆ Energy Saver design

**GENERAL PURPOSE
BASE MOUNTED
Single Phase**

Capacitor Start – Dripproof – Welded Base

HP	RPM	Volts	NEMA Frame	SF	PROT	C Dim.	FLA @ NP	Catalog No.	List Price	Notes
1/4	1725	115/208-230	48	1.35	None	9.25	5.2/2.7-2.6	C147	\$166	7
	1725	115/208-230	48	1.35	Auto	9.25	5.2/2.7-2.6	C148	171	
	1725	115/230	48	1.35	Auto	9.57	5.2/2.6	C145	153	4
	1425	110/220	48	1.35	None	9.66	5.6/2.8	C431	185	50
1/3	1725/1425	115/208-230	48	1.35	None	9.66	6.0/3.2-3.0	C153	181	84
	1725/1425	115/208-230	48	1.35	Auto	9.66	6.0/3.2-3.0	C154	189	84
	1725/1425	115/208-230	56	1.35	Auto	10.32	6.0/3.2-3.0	C159	198	84
	1725/1425	115/208-230	56	1.35	None	10.32	6.0/3.2-3.0	C158	192	84
	1725/1425	110-120/200-240	56	1.35	None	10.77	4.0-3.8/2.0-1.9	E253	221	36,84
	1725	115/230	56	1.00	Man	9.90	6.6/3.3	C105	219	
	1140	115/230	56	1.35	None	11.48	8.6/4.3	C1252	265	
1/2	3450	115/230	56	1.25	Man	10.72	7.4/3.7	C1474	179	
	3450	115/230	48	1.25	None	9.66	7.6/3.8	C162	164	
	2850	110/220	48	1.25	None	10.06	7.8/3.9	C459	203	50
	1725/1425	110-120/200-240	56	1.25	None	10.77	5.8-5.6/2.9-2.8	E262◆	259	36,84
	1725	115/208-230	56	1.25	None	10.38	8.8/4.2-4.4	C167	206	
	1725	115/230	48	1.25	None	10.40	9.2/4.6	C164	224	
	1725	115/230	56	1.25	Auto	10.38	8.8/4.4	C168	208	
	1725	115/230	56	1.25	Man	10.38	8.8/4.4	C169	217	
	1725	115/230	56Z	1.00	None	12.30	8.2/4.1	C393	197	22
	1140	115/230	56	1.25	None	12.76	9.4/4.7	C1263	379	
3/4	3450	115/230	56	1.25	Man	10.72	10.2/5.1	C1475	216	
	3450	115/230	48	1.00	None	16.50	11.2/5.6	C111	200	
	1725/1425	100-120/200-240	56	1.25	None	11.37	9.0-8.8/4.5-4.4	E271◆	325	36,84
	1725	115/208-230	56	1.25	None	10.78	13.2/6.2-6.6	C175	242	
	1725	115/230	56	1.25	Auto	10.78	13.2/6.6	C176	247	
	1725	115/230	56	1.25	Man	10.78	13.2/6.6	C177	262	
	1725	115/208-230	56	1.25	Man	10.34	11.2/5.8-5.6	C1298	359	
	1140	115/230	56	1.15	None	13.96	12.6/6.3	C178	438	36
1	3450	115/208-230	56	1.25	Auto	11.04	12.4/6.4-6.2	C180	228	
	3450	115/230	56Z	1.00	None	12.60	13.4/6.7	C449	221	22
	3450	115/230	56	1.15	Man	11.04	12.8/6.5	C702	275	
	3450	115/208-230	56	1.25	None	11.04	12.4/6.4-6.2	C179	224	
	1725/1425	100-120/200-240	56H	1.15	None	12.66	11.8-11.4/5.9-5.7	E280◆	352	36,84
	1725	115/208-230	56	1.15	None	11.38	13.6/6.7-6.8	C181	279	
	1725	115/208-230	143T	1.15	None	11.77	13.6/6.7-6.8	C188	283	
	1725	115/230	56	1.15	Auto	11.38	13.6/6.8	C182	285	
	1725	115/230	56	1.15	Man	11.38	13.6/6.8	C1480	294	
	1140	115/230	56H	1.15	None	14.93	12.6/6.3	C183	584	36
1.5	3450	115/230	56	1.15	Man	11.91	16.8/8.4	C1477	312	
	3450	115/230	56	1.15	Man	11.91	21.3/10.6	C704	335	
	1725	115/208-230	56H	1.15	Auto	11.90	18.2/9.1	C186	334	36
	1725	115/208-230	56H	1.15	None	11.90	18.2/9.1-9.1	C185	327	36
	1725	115/208-230	145T	1.15	None	12.30	18.2/9.1-9.1	C191	332	36
	1725	115/230	56	1.20	Man	12.45	13.4/6.7	C1299	530	36
2	3450	115/230	56	1.15	None	12.66	21.2/10.6	C187	327	
	3450	115/230	56	1.15	Man	11.91	23.8/11.8	C703	391	
	1725	115/208-230	56HZ	1.15	None	14.33	22.0/10.9-11.0	C193	368	11,36
	1725	115/208-230	56HZ	1.15	Auto	14.33	22.0/10.9-11.0	C381	375	11,36
3	3450	115/230	145T	1.15	None	13.13	29.4/14.7	C194	412	36

◆ Energy Saver design



GE Commercial Motors

By REGAL-BELOIT

Data subject to change without notice

**GENERAL PURPOSE
BASE MOUNTED
Single Phase**



Cat. #C268

Features

- Ball bearings
- Reversible rotation
- Selected Energy Saver (◆) designs available

Applications

Designed for applications having hard or heavy-duty starting loads in dirty or dusty areas, like industrial machinery and pumps, conveyors and farm equipment.

**GENERAL PURPOSE
BASE MOUNTED
Three Phase**



Cat. #K111

Features

- Cast iron 182 through 449 frames comply with MG1-31 @ 460 volts
- Ball bearings
- Motors are non-protected

Applications

Designed for general purpose applications with moderate to high starting torques.

Capacitor Start – Totally Enclosed Fan Cooled – Welded Base

HP	RPM	Volts	NEMA Frame	SF	PROT	Base	FLA @ NP	Catalog No.	List Price	Notes
1/6	1725	115	48	1.00	None	WB	4.0	H116	\$153	39
	850	115/230	56	1.00	None	WB	5.6/2.8	C248	399	
1/4	1725	115	48	1.00	Auto	WB	5.1	H121	168	39
	1725	115	48	1.00	None	WB	5.1	H120	161	39
	1725	115/230	56	1.00	Auto	WB	5.4/2.7	C251	206	
	1725	115/230	56	1.00	None	WB	5.4/2.7	C250	197	
	1725	115/230	48	1.00	Auto	WB	5.4/2.7	C243	198	
	1725	115/230	48	1.00	None	WB	5.4/2.7	C242	190	
	1725	230	48	1.00	Auto	WB	2.7	H243	183	39
	1425	110/220	48	1.00	None	WB	5.4/2.7	C462	219	50
1/3	1140	115/230	56	1.00	None	WB	6.2/3.1	C252	271	
	3450	115	48	1.00	Auto	WB	6.4	H124	175	39
	3450	115	48	1.00	None	WB	6.4	H123	170	39
	1725/1425	100-120/200-240	56	1.35	None	WB	4.0-3.8/2.0-1.9	E258◆	265	36,84
	1725	115/230	56	1.15	Auto	WB	6.0/3.0	C255	219	
	1725	115/230	56	1.00	None	WB	6.0/3.0	C254	211	
	1140	115/230	56	1.00	None	WB	8.6/4.3	C257	301	
	1725/1425	100-120/200-240	56	1.25	None	WB	5.8-5.6/2.9-2.8	E267◆	301	36,84
1/2	1725	115/208-230	56	1.15	None	WB	8.6/4.1-4.3	C261	234	
	1725	115/230	48	1.00	None	WB	8.8/4.4	C260	244	
	1725	115/230	56	1.15	Auto	WB	8.6/4.3	C262	240	
	1140	115/230	56	1.00	None	WB	9.4/4.7	C264	390	
3/4	1725/1425	100-120/200-240	56	1.25	None	WB	9.0-8.8/4.5-4.4	E276◆	335	36,84
	1725	115/208-230	56	1.15	None	WB	11.0/5.4-5.5	C268	279	
	1725	115/230	56	1.00	Auto	WB	11.0/5.5	C269	286	
	1140	115/230	56	1.00	None	WB	10.6/5.3	C271	467	36
1	3450	115/230	56	1.00	Man	WB	13.0/6.5	C274	275	
	1725/1425	100-120/200-240	56	1.15	None	WB	11.8-11.4/5.9-5.7	E285◆	385	36,84
	1725	115/230	143T	1.00	None	WB	13.2/6.6	C295	319	
	1725	115/230	56	1.15	None	WB	13.2/6.6	C275	319	
1.5	1725	115/230	56	1.00	Auto	WB	13.2/6.6	C276	321	
	1725	115/208-230	56H	1.00	Auto	WB	14.5/7.1-7.3	C282	374	36
	1725	115/208-230	56H	1.15	None	WB	14.5/7.1-7.3	C281	327	36
2	1725	115/208-230	145T	1.15	None	WB	14.5/7.1-7.3	C297	386	36
	3450	115/230	56	1.00	Man	WB	17.8/8.9	C284	391	36

◆ Energy Saver design

Dripproof

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	C Dim.	Cat. No.	List Price	Notes
1/4	1725	208-230/460	48	1.35	WB	1.3-1.4/0.7	8.87	K111	\$172	
1/3	3450	208-230/460	48	1.35	WB	1.5-1.8/0.9	9.25	K113	166	
	1725	208-230/460	56	1.35	WB	1.5-1.6/0.8	9.67	K114	190	
1/2	1725	208-230/460	48	1.35	WB	1.5-1.6/0.8	9.25	K527	175	
	3450	208-230/460	48	1.25	WB	2.0-2.0/1.0	9.68	K115	175	
1/2	1725	208-230/460	56	1.25	WB	2.3-2.2/1.1	10.05	K116	213	
	1425	220/380	56	1.25	WB	3.0/1.7	10.05	K318	237	50
	1140	208-230/460	56	1.25	WB	2.6-2.6/1.3	10.78	K117	279	
	3450	208-230/460	56	1.25	WB	2.6-2.6/1.3	10.70	K118	204	
3/4	1725	208-230/460	56	1.25	WB	3.3-3.0/1.5	10.78	K119	235	
	1725	575	56	1.25	WB	1.3	10.70	K392	238	
	1140	208-230/460	56	1.15	WB	2.9-2.8/1.4	11.38	K120	301	
1	850	230/460	145T	1.15	WB	3.4/1.7	14.23	K402	496	67
	3450	208-230/460	56	1.25	WB	3.3-3.2/1.6	11.30	K121	235	
1	1725	208-230/460	56	1.25	WB	3.6-3.8/1.9	10.78	K122	247	
	1725	208-230/460	143T	1.15	WB	3.2-3.1/1.55	11.75	K2005★	261	
	1725	208-230/460	56	1.15	WB	3.2-3.1/1.55	11.38	K2069★	294	
	1140	208-230/460	56H	1.15	WB	3.7-3.8/1.9	11.91	K393	320	
1.5	3450	208-230/460	143T	1.15	WB	4.4-4/2	11.75	K2001★	286	67
	1725	208-230/460	145T	1.15	WB	4.5-4.4/2.2	12.28	K2006★	334	67
	1725	208-230/460	56H	1.15	WB	5.8-5.6/2.8	11.38	K125	274	
2	1425	220/380	145T	1.15	WB	4.5/2.6	13.59	K408	308	50
	3450	208-230/460	56	1.15	WB	6.0-6.0/3.0	11.38	K126	290	
	3450	208-230/460	145T	1.15	WB	5.6-5.2/2.6	13.03	K2002★	334	67
2	1725	208-230/460	145T	1.15	WB	6.4-6/3	13.59	K2007★	361	67
	1725	575	145T	1.15	WB	2.4	13.61	K2010★	286	67
	1425	220/380	145T	1.15	WB	6.4/3.7	14.24	K319	330	50
3	3450	208-230/460	145T	1.15	WB	8.4-7.6/3.8	13.59	K2003★	366	
5	3450	230/460	145T	1.00	WB	12.4/6.2	15.41	K2004★	398	67

★ Meet EPAAct efficiency levels



GE Commercial Motors

By REGAL-BELOIT

Data subject to change without notice

**GENERAL PURPOSE
BASE MOUNTED
Three Phase**



Cat. #E12D4

Features

- Cast iron 182 through 449 frames comply with MG1-31 @ 460 volts
- Ball bearings
- Energy Saver (◆) designs
- Motors are non-protected

Applications

Designed for general purpose applications with moderate to high starting torque.

**GENERAL PURPOSE
BASE MOUNTED
Three Phase**



Cat. #K151

Features

- Cast iron 143 through 449 frames comply with MG1-31 @ 460 volts
- Ball bearings
- 1.0 or 1.15 service factors
- Motors are non-protected

Applications

Designed for general purpose applications in dirty or dusty areas with moderate to high starting torque, where three phase power is available.

Dripproof

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	C Dim.	Cat. No.	List Price	Notes
1/2	1725	208-230/460	56	1.25	WB	1.8-1.8/0.9	10.38	E12D4◆	\$249	
3/4	1725/1425	200-230/460	56	1.25	WB	2.5-2.4/1.2	10.78	E34D4◆	279	84

◆ Energy Saver design

Totally Enclosed Fan Cooled

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	C Dim.	Cat. No.	List Price	Notes
1/4	1725	208-230/460	56	1.00	WB	1.1-1.2/0.6	9.57	K439	\$191	55
	1725	208-230/460	48	1.00	WB	1.3-1.4/0.7	9.92	K151	191	
	1725	230/460	48	1.00	WB	1.2/0.6	9.19	K194	217	55
	1725	575	48	1.00	WB	0.6	9.92	K418	202	
	1140	230/460	56	1.00	WB	1.4/0.7	10.93	K321	268	
1/3	3450	208-230/460	48	1.00	WB	1.5-1.8/0.9	10.2	K153	190	55
	1725	208-230/460	56	1.00	WB	1.5-1.6/0.8	10.73	K154	215	
	1725	208-230/460	56	1.00	WB	1.3-1.4/0.7	9.57	K196	244	
	1140	230/460	56	1.00	WB	1.8/0.9	11.4	K155	280	
1/2	3450	208-230/460	48	1.00	WB	2.0-2.0/1.0	10.6	K156	206	55
	1725	208-230/460	56	1.00	WB	2.1-2.2/1.1	10.93	K158	239	
	1725	208-230/460	56	1.00	WB	1.8-1.8/0.9	9.95	K197	271	
	1725	575	56	1.00	WB	0.8	11	K426	215	
	1140	208-230/460	56	1.00	WB	2.6-2.6/1.3	11.43	K159	301	67
3/4	3450	208-230/460	56	1.00	WB	2.6-2.5/1.3	11.76	K160	226	55
	1725	208-230/460	56	1.00	WB	2.8-2.8/1.4	11.36	K161	255	
	1725	208-230/460	56	1.00	WB	2.4-2.4/1.2	11.38	K198	279	
	1725	575	56	1.00	WB	1.3	11.4	K421	261	
	1140	208-230/460	56	1.00	WB	2.9-2.8/1.4	11.83	K162	309	
1	3450	208-230/460	56	1.00	WB	3.2-3.0/1.5	12.36	K163	266	67
	1725	208-230/460	56	1.15	WB	3.2-3.1/1.55	12.54	K2064★	319	
	1725	208-230/460	143T	1.15	WB	3.2-3.1/1.55	13.34	K2012★	324	
	1725	208-230/460	56	1.00	WB	3.6-3.8/1.9	11.43	K164	266	
	1725	575	143T	1.15	WB	1.25	13.34	K2013★	282	
	1725	575	56	1.00	WB	1.7	11.43	K424	270	
	1140	230/460	56H	1.00	WB	3.6/1.8	13.07	K165	331	
1.5	3450	208-230/460	56	1.15	WB	5.0-4.8/2.4	11.83	K166	285	67
	1725	208-230/460	56H	1.00	WB	4.7-4.4/2.2	13.07	K167	295	
	1725	208-230/460	145T	1.15	WB	4.5-4.4/2.2	13.34	K2014★	357	
	1725	575	145T	1.15	WB	1.75	13.34	K2015★	312	
2	3450	208-230/460	145T	1.15	WB	5.6-5.2/2.6	14.09	K2049★	398	67
	1725	208-230/460	56	1.15	WB	6.2-5.8/2.9	14.38	K1492	318	
	1725	208-230/460	145T	1.15	WB	6.5-5.6/2.8	14.09	K2016★	394	
	1725	575	145T	1.15	WB	2.25	14.09	K2017★	394	
3	3450	230/460	145T	1.15	WB	7.6/3.8	14.64	K2011★	382	67

★ Meet EPA efficiency levels



GE Commercial Motors

By REGAL-BELOIT

Data subject to change without notice

**GENERAL PURPOSE
END MOUNTED – C-FACE
Single Phase**



Cat. #C354



Cat. #E251



Cat. #E250

Features

- Ball bearings
- Reversible rotation
- NEMA C-face mounting, with or without base
- Selected Energy Saver (◆) designs available

Applications

Designed for use on commercial and industrial pumps, centrifugal and hydraulic pumps, machine tools, and other equipment requiring NEMA C-face mounting configuration.

**GENERAL PURPOSE
END MOUNTED – C-FACE
Single Phase**



Cat. #C375

Features

- Ball bearings
- Reversible rotation
- NEMA C-face mounting, with or without base
- Selected Energy Saver (◆) designs available

Applications

Designed for use on commercial and industrial pumps, centrifugal and hydraulic pumps, machine tools, and other equipment requiring NEMA C-face mounting configuration in dirty or dusty areas.

Capacitor Start – Dripproof – No Base

HP	RPM	Volts	NEMA Frame	SF	PROT	Base	FLA @ NP	Catalog No.	List Price	Notes
1/4	1725	115/208-230	56C	1.35	None	NB	5.2/2.7-2.6	C1296	\$174	
	1725	115/208-230	56C	1.35	Auto	NB	5.2/2.7-2.6	C354	179	
1/3	1725/1425	100-120/200-240	56C	1.35	None	NB	4.0-3.8/2.0-1.9	E251◆	263	36,84
	1725/1425	115/208-230	56C	1.35	None	NB	6.0/3.2-3.0	C355	200	84
	1725/1425	115/208-230	56C	1.35	Auto	NB	6.0/3.2-3.0	C356	207	84
1/2	1725/1425	100-120/200-240	56C	1.25	None	NB	5.8-5.6/2.9-2.8	E260◆	300	36,84
	1725	115/208-230	56C	1.25	None	NB	8.8/4.2-4.4	C358	224	
	1725	115/230	56C	1.25	Auto	NB	8.8/4.4	C359	235	
3/4	1725/1425	100-120/200-240	56C	1.25	None	NB	9.0-8.8/4.5-4.4	E269◆	325	36,84
	1725	115/208-230	56C	1.25	None	NB	13.2/6.2-6.6	C361	274	
	1725	115/230	56C	1.25	Auto	NB	13.2/6.6	C362	283	
1	1725/1425	100-120/200-240	56C	1.15	None	NB	11.8-11.4/5.9-5.7	E278◆	374	36,84
	1725	115/230	56C	1.15	Auto	NB	13.6/6.8	C363	316	
	1725	115/208-230	56C	1.15	None	NB	13.6/6.7-6.8	C1297	311	

◆ Energy Saver design

Capacitor Start – Dripproof – Welded Base

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	PROT	Cat. No.	List Price	Notes
1/3	1725/1425	100-120/200-240	56C	1.35	WB	4.0-3.8/2.0-1.9	Man	E250◆	\$276	36,84
	1725/1425	100-120/200-240	56C	1.35	WB	4.0-3.8/2.0-1.9	Auto	E252◆	273	36,84
1/2	1725/1425	100-120/200-240	56C	1.25	WB	5.8-5.6/2.9-2.8	Man	E259◆	316	36,84
	1725/1425	100-120/200-240	56C	1.25	WB	5.8-5.6/2.9-2.8	Auto	E261◆	312	36,84
3/4	1725/1425	100-120/200-240	56C	1.25	WB	9.0-8.8/4.5-4.4	Man	E268◆	338	36,84
	1725/1425	100-120/200-240	56C	1.25	WB	9.0-8.8/4.5-4.4	Auto	E270◆	335	36,84
1	1725/1425	100-120/200-240	56C	1.15	WB	11.8-11.4/5.9-5.7	Man	E277◆	369	36,84
	1725/1425	100-120/200-240	56C	1.15	WB	11.8-11.4/5.9-5.7	Auto	E279◆	385	36,84
2	3450	115/208-230	56C	1.15	WB	15.6/8.8-7.8	Man	C1269	447	
3	3450	208-230	56C	1.15	WB	13.0-12.0	Man	C1270	518	

◆ Energy Saver design

Capacitor Start – Totally Enclosed Fan Cooled

HP	RPM	Volts	NEMA Frame	SF	PROT	Base	FLA @ NP	Catalog No.	List Price	Notes
1/6	1725	115	56C	1.00	None	NB	4.0	H244	\$187	39
1/4	1725	115/230	56C	1.00	None	NB	5.4/2.7	C366	194	
1/3	3450	115/230	56C	1.15	None	NB	5.6/2.8	C1419	189	
	1725/1425	100-120/200-240	56C	1.35	Auto	WB	4.0-3.8/2.0-1.9	E257◆	293	36,84
	1725/1425	100-120/200-240	56C	1.35	Man	WB	4.0-3.8/2.0-1.9	E255◆	295	36,84
1/2	1725	115/230	56C	1.00	None	NB	6.0/3.0	C367	220	
	1725	115/230	56C	1.00	None	WB	6.0/3.0	C1405	224	
	3450	115/230	56C	1.15	Auto	NB	7.4/3.7	C349	215	
3/4	3450	115/230	56C	1.25	Auto	WB	7.4/3.7	C444	210	
	1725/1425	100-120/200-240	56C	1.25	None	NB	5.8-5.6/2.9-2.8	E265◆	316	36,84
	1725	115/230	56C	1.15	Auto	NB	8.6/4.3	C446	253	
	1725	115/230	56C	1.15	None	NB	8.6/4.3	C368	245	
	1725	115/230	56C	1.00	None	WB	8.6/4.3	C375	252	
1	1140	115/230	56C	1.25	None	NB	9.4/4.7	C1422	407	
	1725/1425	100-120/200-240	56C	1.25	None	NB	9.0-8.8/4.5-4.4	E274◆	349	36,84
	1725	115/230	56C	1.00	None	NB	11.0/5.5	C369	290	
1.5	3450	115/230	56C	1.15	Auto	NB	13.0/6.5	C351	275	
	3450	115/230	56C	1.00	Auto	WB	13.0/6.5	C445	282	
	1725/1425	100-120/200-240	56C	1.15	None	NB	11.8-11.4/5.9-5.7	E283◆	400	36,84
	1725/1425	100-120/200-240	56C	1.15	Man	WB	11.8-11.4/5.9-5.7	E282◆	415	36,84
	1725/1425	100-120/200-240	56C	1.15	Auto	WB	11.8-11.4/5.9-5.7	E284◆	412	36,84
1.5	1725	115/230	56C	1.00	None	WB	13.2/6.6	C376	349	
	1725	115/230	56C	1.00	None	NB	13.2/6.6	C370	330	
	3450	115/230	56C	1.00	Auto	NB	16.4/8.2	C855	336	
1.5	3450	115/230	56C	1.00	None	NB	16.4/8.2	C1424	338	
	1725	115/208-230	56C	1.15	None	NB	14.5/7.1-7.3	C371	408	36

◆ Energy Saver design



GE Commercial Motors

By REGAL-BELOIT

Data subject to change without notice

**GENERAL PURPOSE
END MOUNTED – C-FACE
Single Phase**



Cat. #C1423

Features

- Ball bearings
- Reversible rotation
- NEMA C-face mounting, with or without base
- Selected Energy Saver (◆) designs available

Applications

Designed for use on commercial and industrial pumps, centrifugal and hydraulic pumps, machine tools, and other equipment requiring NEMA C-face mounting configuration in dirty or dusty areas.

**GENERAL PURPOSE
END MOUNTED – C-FACE
Three Phase**



Cat. #K1311



Cat. #K1323
(on pg. 30)

Features

- Ball bearings
- NEMA C-face mounting, with or without base
- Selected EPAct (★) designs available
- No protection provided in the motor against excessive heating (thermal overload)

Applications

Designed for use on commercial and industrial pumps, centrifugal and hydraulic pumps, machine tools, speed reducers and other equipment requiring NEMA C-face mounting configuration where three phase power is available.

Capacitor Start – Totally Enclosed Fan Cooled

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	PROT	Cat. No.	List Price	Notes
1/4	1140	115/230	56C	1.00	NB	6.2/3.1	None	C1423	\$281	
1/3	1725/1425	100-120/200-240	56C	1.35	NB	4.0-3.8/2.0-1.9	None	E256◆	281	36,84
1/2	3450	115/230	56C	1.25	WB	7.4/3.7	None	C1420	212	
	1725/1425	100-120/200-240	56C	1.25	WB	5.8-5.6/2.9-2.8	Man	E264◆	327	36,84
	1725/1425	100-120/200-240	56C	1.25	WB	5.8-5.6/2.9-2.8	Auto	E266◆	319	36,84
	1140	115/230	56C	1.00	NB	9.4/4.7	None	C1404	434	
3/4	1725/1425	100-120/200-240	56C	1.25	WB	9.0-8.8/4.5-4.4	Man	E273◆	364	36,84
	1725/1425	100-120/200-240	56C	1.25	WB	9.0-8.8/4.5-4.4	Auto	E275◆	358	36,84
	1725	115/230	56C	1.00	WB	11.0/5.5	None	C1425	298	
	1140	115/230	56C	1.15	NB	12.6/6.3	None	C1412	441	36
2	3450	115/230	56C	1.00	NB	17.8/8.9	Auto	C466	412	36

◆ Energy Saver design

Dripproof

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	C Dim.	Cat. No.	List Price	Notes
1/4	1725	208-230/460	56C	1.00	NB	1.1-1.2/0.6	9.52	K247	\$174	
1/3	1725	208-230/460	56C	1.35	WB	1.5-1.6/0.8	9.95	K1305	203	
	1725	208-230/460	56C	1.35	NB	1.5-1.6/0.8	9.52	K248	191	
1/2	3450	208-230/460	56C	1.60	NB	2.0-2.0/1.0	10.31	K216	179	
	3450	208-230/460	56C	1.60	WB	2.2-2.5/1.3	10.38	K1306	191	
	1725	208-230/460	56C	1.25	WB	2.3-2.2/1.1	9.95	K1307	233	
	1725	208-230/460	56C	1.25	NB	2.3-2.2/1.1	9.90	K249	221	
	1140	208-230/460	56C	1.25	NB	2.6-2.6/1.3	10.78	K1299	281	
3/4	3450	208-230/460	56C	1.50	NB	2.6-2.6/1.3	10.70	K218	215	
	1725	208-230/460	56C	1.25	WB	3.3-3.0/1.5	10.78	K1308	246	
	1725	208-230/460	56C	1.25	NB	3.3-3.0/1.5	10.73	K250	242	
	1140	208-230/460	56C	1.15	NB	2.9-2.8/1.4	11.38	K1300	304	
	1140	208-230/460	143TC	1.15	NB	2.9-2.8/1.4	11.50	K1301	312	
1	3450	208-230/460	56C	1.40	NB	3.3-3.2/1.6	11.30	K220	242	
	1725	208-230/460	143TC	1.15	WB	3.2-3.1/1.55	11.50	K2021★	276	
	1725	208-230/460	56C	1.15	NB	3.6-3.8/1.9	10.73	K251	257	
	1725	208-230/460	143TC	1.15	NB	3.6-3.8/1.9	12.42	K634	276	
	1725	208-230/460	56HC	1.15	WB	3.6-3.8/1.9	10.78	K635	257	
	1140	208-230/460	145TC	1.15	NB	3.7-3.6/1.8	11.50	K2024★	344	
1.5	3450	208-230/460	56C	1.30	NB	5.0-4.8/2.4	10.73	K222	270	
	3450	208-230/460	143TC	1.15	NB	4.4-4/2	11.50	K2018★	281	
	3450	208-230/460	56C	1.15	WB	5.2-5/2.5	10.44	K690	275	
	1725	208-230/460	145TC	1.15	WB	4.5-4.4/2.2	12.03	K2022★	324	
	1725	208-230/460	56C	1.15	NB	5.8-5.6/2.8	11.33	K521	285	
	1725	208-230/460	145TC	1.15	NB	5.2/2.6	11.95	K622	324	
	1725	208-230/460	56HC	1.15	WB	5.2/2.6	11.91	K646	285	
2	3450	208-230/460	56C	1.15	WB	6.6-6.0/3.0	11.38	K1311	300	
	3450	208-230/460	145TC	1.15	NB	5.6-5.2/2.6	12.78	K2019★	346	
	3450	208-230/460	56C	1.20	NB	6.0-6.0/3.0	11.33	K224	326	
	1725	208-230/460	145TC	1.15	WB	6.4-6/3	13.34	K2023★	326	
	1725	230/460	56C	1.15	NB	6.4/3.2	13.81	K644	326	
	1725	208-230/460	56HC	1.15	WB	6.2-5.8/2.9	13.86	K648	326	
3	3450	208-230/460	145TC	1.15	NB	8.4-7.6/3.8	13.34	K2020★	375	
	3450	208-230/460	56C	1.15	NB	8.9-8.2/4.1	12.61	K226	354	

★ Meet EPAct efficiency levels



GE Commercial Motors

By REGAL-BELOIT

Data subject to change without notice

**GENERAL PURPOSE
END MOUNTED – C-FACE**

Three Phase

Totally Enclosed Fan Cooled

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	C Dim.	Cat. No.	List Price	Notes
1/4	1725	208-230/460	56C	1.00	NB	1.1-1.2/0.6	9.52	K252	\$206	55
	1140	208-230/460	56C	1.35	NB	1.5-1.4/0.7	11.01	K1314	285	
1/3	1725	208-230/460	56C	1.35	WB	1.5-1.6/0.8	11.01	K1322	228	
	1725	208-230/460	56C	1.00	NB	1.5-1.6/0.8	10.60	K253	217	
	1725	575	56C	1.00	NB	0.6	10.60	K522	217	
	1140	208-230/460	56C	1.35	NB	2.4-2.2/1.1	11.01	K1315	290	
1/2	3450	208-230/460	56C	1.25	WB	2.2-2.5/1.3	11.01	K1323	221	
	1725	208-230/460	56C	1.25	WB	2.3-2.2/1.1	11.01	K1324	254	
	1725	208-230/460	56C	1.25	NB	2.1-2.2/1.1	10.93	K254	249	
	1725	575	56C	1.00	NB	0.8	11.01	K469	252	
	1140	208-230/460	56C	1.25	NB	2.6-2.6/1.3	11.44	K1316	313	
1/2	1140	208-230/460	56C	1.25	WB	2.6-2.6/1.3	11.44	K1325	317	
	3/4	3450	208-230/460	56C	1.25	WB	2.6-2.6/1.3	11.40	K499	239
3/4	3450	200-230/460	56C	1.50	NB	2.6-2.6/1.3	11.36	K231	225	
	1725	208-230/460	56C	1.25	NB	2.8-2.8/1.4	11.36	K255	262	
3/4	1725	208-230/460	56C	1.25	WB	3.3-3.0/1.5	11.41	K258	266	
	1725	575	56C	1.00	NB	1.3	11.36	K523	265	
3/4	1140	208-230/460	143TC	1.15	NB	2.9-2.8/1.4	12.56	K1318	324	
	1140	208-230/460	56C	1.15	WB	2.9-2.8/1.4	12.44	K1326	324	
	1140	208-230/460	56C	1.15	NB	2.9-2.8/1.4	12.44	K1317	319	
	1	3450	208-230/460	56C	1.25	WB	3.2-3.0/1.5	12.40	K500	272
1	3450/2850	208-220/440	56C	1.00	NB	3.6-3.6/1.8	11.36	K633	270	
	1725	208-230/460	143TC	1.15	NB	3.7-3.2/1.6	11.96	K2029★	291	
	1725	208-230/460	143TC	1.25	WB	3.7-3.2/1.6	13.84	K2032★	298	
	1725	208-230/460	56C	1.25	NB	3.6-3.8/1.9	11.44	K256	277	
	1725	575	56C	1.00	NB	1.7	11.44	K524	281	
	1725	208-230/460	56C	1.25	WB	3.6-3.8/1.9	11.41	K259	282	
	1725	208-230/460	143TC	1.15	WB	3.4-3.2/1.6	12.12	K2039	298	
	1140	208-230/460	145TC	1.15	WB	3.9-4.0/2.0	13.84	K2036★	361	
	1140	208-230/460	56C	1.15	NB	3.9-3.8/1.9	12.44	K1490	326	
	1140	208-230/460	145TC	1.15	NB	3.7-3.6/1.8	12.56	K2035★	352	
	1140	208-230/460	56C	1.25	WB	4.3-4.5/2.7	13.72	K1222	326	
	1.5	3450	208-230/460	143TC	1.15	NB	5.0-4.8/2.4	12.56	K2025★	343
3450		208-230/460	143TC	1.15	WB	5.0-4.8/2.4	13.84	K2026★	357	
3450		200-230/460	56C	1.30	NB	4.8-4.2/2.1	12.44	K235	293	
3450		208-230/460	56C	1.15	WB	5.0-4.8/2.4	11.84	K1328	309	
3450/2850		208-220/460	56C	1.15	NB	4.8-4.6/2.3	11.82	K642	298	
1725		208-230/460	145TC	1.25	WB	4.5-4.4/2.2	13.84	K2031★	338	
1725		208-230/460	56C	1.00	WB	4.7-4.4/2.2	12.44	K260	312	
1725		208-230/460	145TC	1.15	NB	4.5-4.4/2.2	13.09	K2048★	349	
1725		208-230/460	56C	1.00	NB	4.7-4.4/2.2	12.44	K257	300	
1140		230/460	56C	1.15	NB	5.4/2.7	14.89	K1221	305	
2	3450	208-230/460	56C	1.15	WB	5.8-5.4/2.7	12.97	K501	328	
	3450	208-230/460	145TC	1.15	NB	6.6-6.0/3.0	13.84	K2027★	397	
	3450	200-230/460	56C	1.20	NB	5.8-5.4/2.7	12.97	K237	335	
	3450	208-230/460	145TC	1.15	WB	5.6-5.2/2.6	13.84	K2028★	404	
	3450/2850	208-230/460	56C	1.15	NB	6.0-6.0/3.0	12.32	K637	340	
	1725	208-230/460	56C	1.15	NB	6.2-5.8/2.9	14.25	K1491	345	
	1725	208-230/460	145TC	1.15	NB	6-5.6/2.8	13.84	K2033★	360	
	1725	208-230/460	145TC	1.15	WB	6.2-5.8/2.9	13.84	K2034★	371	
	1725	208-230/460	145TC	1.15	NB	6.2-5.8/2.9	14.4	K330	360	
	1725	208-230/460	145TC	1.15	NB	6.4-6.0/3.0	12.62	K2043	326	
3	3450	230/460	56C	1.00	NB	8.0/4.0	14.25	K239	384	
	3450	230/460	145TC	1.15	NB	7.6/3.8	13.75	K2042	513	
	1725	230/460	56C	1.00	NB	8.2/4.1	14.89	K640	389	

★ Meet EPA efficiency levels



GE Commercial Motors

By REGAL-BELOIT

Data subject to change without notice