

PUMP MOTORS
CENTRIFUGAL PUMP
Single Phase



Cat. #C332



Cat. #C465

Features

- Ball bearings
- Reversible rotation
- NEMA C-face with standard shaft or threads

Applications

Designed for use on commercial and industrial pumps, centrifugal and hydraulic pumps, machine tools, and other equipment requiring NEMA C-face mounting configuration.

Capacitor Start – Dripproof

HP	RPM	Volts	NEMA Frame	SF	C Dim.	Base	FLA @ NP	Catalog No.	List Price	Notes
1/3	3450	115/230	56C	1.75	10.71	NB	6.4/3.2	C328	\$156	
	3450	115/230	56J	1.75	11.22	NB	6.4/3.2	C329	161	60
	1725/1425	115/208-230	56J	1.35	10.82	NB	6.0/3.2-3.0	C683	235	60,84
1/2	3450	115/230	56C	1.60	10.31	NB	7.6/3.8	C330	171	
	3450	115/230	56J	1.60	10.82	NB	7.6/3.8	C331	173	60
3/4	3450	115/230	56C	1.50	11.84	NB	11.2/5.6	C332	201	
	3450	115/230	56J	1.50	12.40	NB	11.2/5.6	C333	204	60
	2850	110/220	56C	1.50	12.60	NB	9.8/4.9	C732	229	50
1	3450	115/230	56C	1.40	12.59	NB	13.2/6.6	C334	222	
	3450	115/230	56J	1.40	13.14	NB	13.2/6.6	C335	228	60
1.5	3450	115/230	56C	1.30	11.38	NB	18.4/9.2	C336	310	
	3450	115/230	56J	1.30	11.89	NB	18.4/9.2	C337	314	60
2	3450	115/230	56C	1.20	13.22	NB	21.2/10.6	C338	383	
	3450	115/230	56J	1.20	13.73	NB	21.2/10.6	C339	398	60
3	3450	115/230	56C	1.15	12.66	NB	29.4/14.7	C340	418	36
	3450	115/230	56J	1.15	13.17	NB	29.4/14.7	C341	429	36,60


Capacitor Start – Totally Enclosed Fan Cooled

1/3	3450	115/230	56J	1.00	11.87	NB	5.6/2.8	C1336	\$189	
1/2	3450	115/230	56J	1.15	11.90	NB	7.4/3.7	C465	235	60
3/4	3450	115/230	56C	1.00	11.76	NB	9.8/4.9	C847	250	
1	3450	115/230	56J	1.15	12.95	NB	13.0/6.5	C352	270	60
2	3450	115/230	56J	1.00	14.79	NB	17.8/8.9	C878	405	36,60

- ★ Meet EPAct efficiency levels
- ◆ Energy Saver design



**PUMP MOTORS
CENTRIFUGAL PUMP**




Features

- Ball bearings
- NEMA C-face with standard shaft or threads

Applications

Designed for use on commercial and industrial pumps, centrifugal and hydraulic pumps, machine tools, speed reducers and other equipment requiring NEMA C-face mounting configuration.

Cat. #K225



Cat. #K245

Dripproof

HP	RPM	Volts	NEMA Frame	SF	C Dim.	Base	FLA @ NP	Catalog No.	List Price	Notes
1/3	3450	208-230/460	56C	1.75	9.90	NB	1.5-1.8/0.9	K215	\$170	
	3450	208-230/460	56J	1.75	10.40	NB	1.5-1.8/0.9	K748	173	61
1/2	3450	208-230/460	56J	1.60	10.82	NB	2.0-2.0/1.0	K217	198	61
	1725	208-230/460	56J	1.25	10.41	NB	2.3-2.2/1.1	K553	266	61
3/4	3450	208-230/460	56J	1.50	11.22	WB	2.6-2.6/1.3	K1483	221	61
	3450	208-230/460	56J	1.50	11.22	NB	2.6-2.6/1.3	K219	216	61
	1725	208-230/460	56J	1.25	11.24	NB	3.3-3.0/1.5	K555	313	61
1	3450	208-230/460	56J	1.40	11.82	NB	3.3-3.2/1.6	K221	249	61
	1725	208-230/460	56J	1.15	11.24	NB	3.6-3.8/1.9	K750	324	61
1.5	3450	208-230/460	56J	1.15	11.24	WB	5.0-4.8/2.4	K1484	319	61
	3450	208-230/460	56J	1.30	11.24	NB	5.0-4.8/2.4	K223	314	61
	1725	208-230/460	56J	1.15	11.84	NB	5.8-5.6/2.8	K751	358	61
2	3450	208-230/460	56J	1.20	11.84	NB	6.0-6.0/3.0	K225	373	61
3	3450	208-230/460	56J	1.15	13.12	NB	8.9-8.2/4.1	K227	442	61

Totally Enclosed Fan Cooled

1/3	3450	208-230/460	56C	1.00	10.60	NB	1.5-1.8/0.9	K228	\$190	
1/2	3450	200-230/460	56C	1.60	10.93	NB	2.1-2.0/1.0	K229	206	
	3450	200-230/460	56J	1.60	11.40	NB	2.1-2.0/1.0	K230	222	61
	3450	200-220/440	56J	1.00	11.44	WB	2.1-2.0/1.0	K1333	221	
	1725	208-230/460	56J	1.00	11.52	NB	2.3-2.2/1.1	K550	270	61
3/4	3450	208-230/460	56J	1.50	11.90	NB	2.6-2.6/1.3	K232	245	61
	3450/2850	208-230/440	56J	1.00	11.90	WB	2.8-2.9/1.5	K630	245	
1	3450	200-230/460	56C	1.40	12.36	NB	3.2-3.0/1.5	K233	270	
	3450	200-230/460	56J	1.40	12.90	NB	3.2-3.0/1.5	K234	282	61
	3450	200-230/460	56J	1.40	12.90	WB	3.2-3.0/1.5	K245	288	61
1.5	3450	200-230/460	56J	1.30	12.95	NB	4.8-4.2/2.1	K236	303	61
	3450	200-230/460	56J	1.30	12.95	WB	4.8-4.2/2.1	K246	303	61
2	3450	200-230/460	56J	1.20	13.48	NB	5.8-5.4/2.7	K238	344	61
3	3450	230/460	56J	1.00	14.79	NB	8.0/4.0	K240	417	61

**PUMP MOTORS
JET PUMP**



Cat. #C1169

Features

- Two-compartment design for easy servicing
- Ball bearings
- CW rotation only
- NEMA C-face with standard shaft or threads, or square flange mounting
- 50°C ambient

Applications

Designed for domestic and light industrial water systems requiring 56C, 56J or square flange mounting.

NEMA C-Face Mounting – Dripproof

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	Catalog No.	List Price	C Dim.	Notes
1/3	3450	115	56C	1.75	NB	6.2	H439	\$127	11.03	
	3450	115	56J	1.75	NB	6.2	H440	129	11.54	
	3450	115	56J	1.75	WB	6.2	H685	134	11.54	
	3450	115/230	56C	1.75	NB	6.2/3.1	C1081	140	11.03	
1/2	3450	115/230	56J	1.75	NB	6.2/3.1	C1087	144	11.54	
	3450	115/230	56C	1.60	NB	8.2/4.1	C1082	147	11.03	
	3450	115/230	56J	1.60	NB	8.2/4.1	C1088	150	11.54	
	3450	115/230	56J	1.60	WB	8.2/4.1	C1462	154	11.54	
3/4	3450	115/230	56C	1.50	NB	11.6/5.8	C1083	163	12.01	
	3450	115/230	56J	1.50	NB	11.6/5.8	C1089	167	12.42	
	3450	115/230	56J	1.50	WB	11.6/5.8	C1463	172	12.42	
1	3450	115/230	56C	1.40	NB	14.2/7.1	C1084	187	13.47	
	3450	115/230	56J	1.40	NB	14.2/7.1	C1090	191	13.98	
	3450	115/230	56J	1.40	WB	14.2/7.1	C1464	194	13.98	
1.5	3450	115/230	56C	1.30	NB	15.8/7.9	C1085	248	13.47	36
	3450	115/230	56J	1.30	NB	15.8/7.9	C1091	253	13.98	36
	3450	115/230	56J	1.30	WB	15.8/7.9	C1465	256	13.98	36
2	3450	115/230	56C	1.20	NB	19.2/9.6	C1086	303	13.47	36
	3450	115/230	56J	1.20	NB	19.2/9.6	C1092	307	13.98	36
	3450	115/230	56J	1.20	WB	19.2/9.6	C1466	311	13.98	36

Square Flange Mounting – Dripproof

1/3	3450	115/230	56Z	1.95	NB	6.4/3.2	C1168	\$144	11.59	
1/2	3450	115/230	56Z	1.90	NB	10.8/5.4	C1169	145	11.59	
3/4	3450	115/230	56Z	1.65	NB	12.6/6.3	C1170	152	12.59	
1	3450	115/230	56Z	1.65	NB	16.4/8.2	C1171	172	12.59	
1.5	3450	230	56Z	1.50	NB	7.6	C1172	197	13.12	36
2	3450	230	56Z	1.30	NB	8.7	C1173	262	13.12	36



GE Commercial Motors

By REGAL-BELOIT

Data subject to change without notice

PUMP MOTORS
OEM REPLACEMENT
Single Phase



Features

- Sleeve or ball bearings
- Completely interchangeable with OEM units
- Motors are auto protected

Applications

These units are all designed as specific replacements for many OEM carbonator pumps, sump pumps, and hot water circulators.

PUMP MOTORS
OIL BURNER
Single Phase



Features

- Sleeve or ball bearings
- Reversible rotation
- Manual reset thermal overload protection
- 21" motor leads, except catalog #4779

Applications

Designed for direct NEMA 48M or 48N mounting to domestic oil burner.

Carbonator Pump – Split Phase – Dripproof

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	Cat. No.	List Price	C Dim.	Notes
1/4	1725/1425	208-240	48Y	1.00	RB	2.3-2.4	H451	\$107	7.69	84,4
	1725/1425	115/230	48Z	1.00	RB	4.3/2.2	H344	93	8.75	
	1725	115	48Y	1.00	RB	5.0	4725	93	7.69	4
	1725	115	48Y	1.00	WB	5.0	H679	89	7.69	4
1/3	1725/1425	100-120/200-240	48Y	1.00	WB	5.5-5.6/2.7-2.8	H681	112	7.69	84,4
	1725/1425	100-120/200-240	48Y	1.00	RB	5.5-5.6/2.7-2.8	H683	131	7.94	
	1725/1425	100-120/200-240	48Y	1.00	RB	5.5-5.6/2.7-2.8	4805	117	7.69	84,4
	1725/1425	220-240	48Y	1.00	RB	2.7-2.7	H450	113	7.69	84,4
	1725	115	48Y	1.15	RB	5.6	4406	102	7.69	4
	1725	115	48Y	1.00	WB	5.6	H680	98	7.69	4
1725	115	48Y	1.00	RB	6.1	H682	118	7.69		
1/2	1725/1425	100-120/200-240	48Y	1.00	RB	7.1-7.2/3.4-3.6	H684	152	8.75	84
3/4	1725	115/230	48Y	1.00	RB	10.4/5.2	H714	203	9.15	

Carbonator Pump – Split Phase – Dripproof – Double Shaft

1/3	1725/1425	100-120/200-240	48Y	1.00	WB	5.5-5.6/2.7-2.8	H712	\$120	9.47	84,4
-----	-----------	-----------------	-----	------	----	-----------------	------	-------	------	------

Sump Pump (with float switch & cord set) – Split Phase – Dripproof

1/3	1725	115	48K	1.00	NB	5.7	H641	\$102	9.60	60,4
	1725	115	48K	1.00	NB	5.7	H642	109	9.60	62,4
	1725	115	48K	1.00	NB	5.0	H950	102	7.90	4,60
1/2	1725	115	48K	1.00	NB	7.3	H951	142	8.70	4,60

Hot Water Circulating Pump – Split Phase – Dripproof

1/12	1725	115	48Y	1.40	RR	2.1	4722	\$114	7.29	4
1/8	1725	115	48Y	1.40	RR	2.6	4404	125	8.90	4
1/4	1725	115	48Y	1.00	RR	5.7	H716	186	9.01	4
1/3	1725	115	48Y	1.00	RR	6.2	H717	198	9.41	4

Capacitor Start – Dripproof

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	Cat. No.	List Price	C Dim.	Notes
1/3	3450	115/230	48N	1.35	NB	6.0/3.0	4788	\$141	10.13	
1/2	3450	115/230	48N	1.25	NB	8.2/4.1	4781	163	10.13	

Split Phase – Totally Enclosed Non-Ventilated (when mounted)

1/8	3450	115	48N	1.00	NB	2.4	4773	\$ 84	7.60	4
	1725	115	48N	1.00	NB	2.9	4782	78	7.40	4
1/7	3450	115	48M	1.00	NB	2.4	4779	77	7.15	60,81,4
1/6	1725	115	48N	1.00	NB	3.3	4784	82	7.60	4
	3450	115	48N	1.00	NB	4.1	4785	107	8.13	4
1/4	1725	115	48N	1.00	NB	4.1	4786	107	7.90	4
	3450	115	48N	1.00	NB	4.9	4774	116	8.38	4
1/3	1725	115	48N	1.00	NB	4.8	4787	116	8.13	4

Permanent Split Capacitor – Dripproof

1/7	3450	115	48M	1.00	NB	1.7	4777	\$64	6.61	
-----	------	-----	-----	------	----	-----	------	------	------	--



GE Commercial Motors

By REGAL-BELOIT

**PUMP MOTORS
SPA, ABOVE GROUND POOL & JETTED TUB**



Cat. #C1455

Features

- Two-compartment design for easy servicing
- Ball bearings
- One or two speed
- CW rotation only
- Extended clamp screws
- Spa motor rated for 50 degree C ambient
- Shaft type is threaded

Applications

Designed for spas, jetted tubs, and above ground swimming pools.

Capacitor Start – Single Speed – Welded Base – Spa – 60Hz

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	Cat. No.	List Price	C Dim.	Notes
1/2	3450	115	56Y	1.00	WBE	6.9	C1427	\$165	10.80	
3/4	3450	115	56Y	1.00	WBE	9.0	C1428	173	10.80	
	3450	115/230	56Y	1.00	WBE	9.0/4.5	C1453	177	10.80	
1	3450	115/230	56Y	1.00	WBE	11.7/5.9	C1454	185	11.80	
	3450	115	56Y	1.00	WBE	11.7	C1429	181	11.78	
1.5	3450	115/230	56Y	1.00	WBE	14.4/7.2	C1455	209	13.20	36
	3450	115	56Y	1.00	WBE	14.4	C1430	205	13.24	36
2	3450	230	56Y	1.00	WBE	8.5	C1456	231	13.20	36
3	3450	230	56Y	1.00	WBE	12.5	C1503	286	14.10	36,42

Capacitor Start – Two Speed – Welded Base – Spa – 60Hz

1/2	3450/1725	115	56Y	1.00	WBE	6.6/2.8	C1317	\$175	11.80	
3/4	3450/1725	115	56Y	1.00	WBE	8.8/2.6	C1322	203	11.80	
	3450/1725	230	56Y	1.00	WBE	4.4/1.3	C1457	207	11.80	
1	3450/1725	115	56Y	1.00	WBE	11.9/3.3	C1323	228	13.20	
	3450/1725	230	56Y	1.00	WBE	5.8/1.9	C1324	258	13.20	
1.5	3450/1725	115	56Y	1.00	WBE	16.0/6.2	C1316	258	13.20	36
	3450/1725	230	56Y	1.00	WBE	6.9/2.6	C1326	263	13.20	36
2	3450/1725	230	56Y	1.00	WBE	8.8/2.6	C1327	281	13.24	36
3	3450/1725	230	56Y	1.00	WBE	13.0/3.7	C1504	299	14.86	36,42

Capacitor Start – Dripproof – Two Speed – Welded Base – Spa – 50Hz

3/4	3000/1500	220-240	56Y	1.00	WBE	6.1/1.3	C1509	\$209	13.24	
1	3000/1500	220-240	56Y	1.00	WBE	6.7/1.7	C1328	238	13.24	
1.5	3000/1500	220-240	56Y	1.00	WBE	7.3/2.8	C1329	266	12.08	36,42
2	3000/1500	220-240	56Y	1.00	WBE	9.5/3.5	C1330	295	12.08	36,42

**PUMP MOTORS
SPA, ABOVE GROUND POOL & JETTED TUB**



Cat. #H910



Cat. #C1902

Features

- Two-compartment design for easy servicing
- Ball bearings
- One or two speed
- CW rotation only
- Extended clamp screws
- Spa motor rated for 50 degree C ambient
- UL1081 recognized rainshield
- Shaft type is threaded

Applications

Designed for spas, jetted tubs, and above ground swimming pools.

Split Phase – Dripproof – Above Ground Pool Replacement For Doughboy/LoMart

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	Cat. No.	List Price	C Dim.	Notes
1	3450	115	48Y	1.00	ECS	10.0	H920	\$135	9.67	
	3450	115	48Y	1.00	ECS	10.0	H911	121	9.88	62
1.5	3450	115	48Y	1.00	ECS	15.8	H923	136	11.30	

Dripproof – Single Speed – Welded Base – Above Ground Pool & Jetted Tub

1/2	3450	115	56Y	1.00	WBE	7.5	H890	\$115	9.88	39
3/4	3450	115	56Y	1.00	WBE	9.9	H909	128	10.31	39
	3450	115	56Y	1.00	WBE	12.4	H910	143	10.71	39
1.5	3450	115	56Y	1.00	ECS	15.8	H921	157	11.84	39
	3450	230	56Y	1.00	WBE	8.6	C1901	150	11.30	38
	3450	115/230	56Y	1.00	WBE	16.0/8.0	C1905	181	11.84	38

Dripproof – Two Speed – Welded Base – Above Ground Pool & Jetted Tub

1/2	3450/1725	115	56Y	1.00	WBE	6.6/2.8	C1906	\$162	11.31	38
3/4	3450/1725	115	56Y	1.00	WBE	9.4/3.2	H922	133	10.71	39
	3450/1725	115	56Y	1.00	WBE	8.8/2.6	C1902	172	11.30	38
1	3450/1725	115	56Y	1.00	WBE	11.9/3.3	C1903	183	11.30	38



GE Commercial Motors

By REGAL-BELOIT

**PUMP MOTORS
POOL & SPA – SQUARE FLANGE**



Cat. #C1244

Features

- Two-compartment design for easy servicing
- Water barrier seal system
- Voltage selection plug
- Ball bearings
- CW rotation only
- 50 degree C ambient
- All copper windings
- Threaded shaft motors are 303 stainless
- UL 1081 approved

Applications

Designed for inground swimming pools requiring square flange mounting.

Capacitor Start – Square Flange Mounting – Single Speed – Full Rated

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	Cat. No.	List Price	C Dim.	Notes
1/3	3450	115/230	56Z	1.95	NB	5.7/3.8	C1484	\$162	11.60	
1/2	3450	115/230	56Z	1.90	NB	9.8/4.9	C1304	167	12.60	
	3450	115/208-230	56Z	1.90	NB	6.0/3.2-3.0	C1446	188	12.60	36
3/4	3450	115/230	56Z	1.65	NB	10.4/5.2	C1305	192	12.60	100
	3451	115/208-230	56Z	1.65	NB	8.8/4.6-4.4	C1499	215	12.60	36
1	3451	115/230	56Z	1.65	NB	16.2/8.1	C1306	221	13.10	100
	3452	115/208-230	56Z	1.65	NB	10.6/5.5-5.3	C1500	248	13.10	36
1.5	3452	115/208-230	56Z	1.50	NB	14.3/7.3-7.1	C1307	294	14.90	36
2	3453	115/208-230	56Z	1.30	NB	18.8/9.6-9.4	C1308	365	14.90	36
3	3453	208-230	56Z	1.15	NB	13.5-13.0	C1449	425	16.10	36

Capacitor Start – Square Flange Mounting – Single Speed – Up Rated

1/2	3450	115/230	56Z	1.30	NB	7.6/3.8	C1243	\$162	11.60	
3/4	3450	115/230	56Z	1.27	NB	10.2/5.1	C1244	167	11.60	
1	3450	115/230	56Z	1.25	NB	12.0/6.0	C1245	192	12.60	
1.5	3450	115/230	56Z	1.10	NB	17.0/8.5	C1246	221	13.10	
2	3450	115/230	56Z	1.10	NB	18.8/9.4	C1247	294	14.90	36
	3450	208-230	56Z	1.04	NB	9.0-8.8	C1284	365	14.90	36
2.5	3450	208-230	56Z	1.00	NB	11.5-11.3	C1335	388	14.90	36
3	3450	208-230	56Z	1.00	NB	13.2-13.0	C1445	425	16.10	36

Capacitor Start – Square Flange Mounting – Two Speed – Full Rated

3/4	3450/1725	115	56Z	1.65	NB	9.0/2.5	C1450	\$321	14.90	36
	3450/1725	230	56Z	1.65	NB	5.6/1.3	C1310	315	13.62	
1	3450/1725	230	56Z	1.25	NB	6.0/1.8	C1311	336	13.12	
1.5	3450/1725	230	56Z	1.50	NB	7.0/2.2	C1312	406	15.46	36
2	3450/1725	230	56Z	1.30	NB	8.7/2.9	C1313	444	16.10	36

**PUMP MOTORS
POOL & SPA – C-FACE**



Cat. #C1096

Features

- Two-compartment design for easy servicing
- Water barrier seal system
- Ball bearings
- CW rotation only
- 50 degree C ambient
- All copper windings
- Threaded shaft motors are 303 stainless
- UL 1081 approved

Applications

Designed for inground swimming pools requiring c-face mtg.

Capacitor Start – NEMA 56C & 56J Frame – Single Speed – Full Rated

HP	RPM	Volts	NEMA Frame	SF	Base	FLA @ NP	Cat. No.	List Price	C Dim.	Notes
1/2	3450	115/230	56C	1.60	NB	7.4/3.7	C1093	\$162	12.00	
	3450	115/230	56C	1.90	NB	5.9/3.0	C1485	179	13.50	36
	3450	115/230	56J	1.60	NB	7.4/3.7	C1098	167	12.40	
	3450	115/230	56J	1.90	NB	5.9/3.0	C1486	185	14.00	36
3/4	3450	115/230	56C	1.50	NB	9.9/4.9	C1094	182	12.00	
	3450	115/230	56C	1.65	NB	7.5/3.8	C1436	201	13.50	36
	3450	115/230	56J	1.50	NB	9.9/4.9	C1099	188	12.40	
	3450	115/230	56J	1.65	NB	7.5/3.8	C1437	207	14.00	36
1	3450	115/230	56C	1.50	NB	10.6/5.3	C1095	190	13.50	36
	3450	115/230	56C	1.65	NB	10.2/5.1	C1487	209	13.80	36
	3450	115/230	56J	1.50	NB	10.6/5.3	C1100	197	14.00	36
	3450	115/230	56J	1.65	NB	10.2/5.1	C1488	214	14.30	36
1.5	3450	115/230	56C	1.50	NB	14.8/7.4	C1096	277	13.80	36
	3450	115/230	56J	1.50	NB	14.8/7.4	C1101	283	14.30	36
2	3450	230	56C	1.30	NB	8.8	C1097	340	13.80	36
	3450	230	56J	1.30	NB	8.8	C1102	346	14.30	36
3	3450	230	56C	1.15	NB	13.0	C1439	415	15.60	36
	3450	230	56J	1.15	NB	13.0	C1440	419	16.10	36

Capacitor Start – NEMA 56J Frame – Single Speed – Up Rated

3/4	3450	115/230	56J	1.00	NB	9.8/4.9	C1321	\$166	12.42	
1	3450	115/230	56J	1.00	NB	12.7/6.3	C1318	188	13.98	
1.5	3450	115/230	56J	1.00	NB	15.8/7.9	C1319	214	13.98	36
2	3450	115/230	56J	1.00	NB	19.2/9.6	C1320	286	13.98	36
2.5	3450	230	56J	1.00	NB	8.8	C1149	356	14.31	36

Capacitor Start – NEMA 56C & 56J Mounting – Two Speed – Full Rated

1/2	3450/1725	115	56C	1.65	NB	7.4/2.4	C1103	\$290	12.01	
	3450/1725	115	56J	1.65	NB	7.4/2.4	C1108	295	12.42	
3/4	3450/1725	115	56C	1.65	NB	10.2/3.4	C1104	275	15.10	
	3450/1725	230	56C	1.65	NB	5.1/1.7	C1105	299	13.47	
	3450/1725	115	56J	1.65	NB	10.2/3.4	C1109	301	15.61	
	3450/1725	230	56J	1.65	NB	5.1/1.7	C1110	304	13.98	
1	3450/1725	230	56C	1.50	NB	5.2/2.6	C1106	305	13.47	36
	3450/1725	230	56J	1.50	NB	5.2/2.6	C1111	309	13.98	36
1.5	3450/1725	230	56C	1.50	NB	7.0/2.2	C1107	356	15.08	36
	3450/1725	230	56J	1.50	NB	7.0/2.2	C1112	362	15.59	36
2	3450/1725	230	56C	1.30	NB	8.7/2.9	C1442	501	15.44	36
	3450/1725	230	56J	1.30	NB	8.7/2.9	C1443	507	15.59	36



GE Commercial Motors

By REGAL-BELOIT